

UNIVERSAL AND SWITCH HEAD STICKS

⚠ WARNING

Cancer and Reproductive Harm: www.P65Warnings.ca.gov



KEY FEATURES

- ✓ Universal end fitting on all models
- ✓ ASTM F711 compliant
- ✓ Available in 4', 6', 8', 10', and 12' lengths
- ✓ Fits a wide range of lineman tools with a universal attachment
- ✓ Includes hanger for quick placement

Slingco's Universal and Switch Head Sticks are designed for safety and ease of operation in high-voltage environments. These hot sticks are trusted by linemen for performing switching, testing, grounding, and disconnect operations on live lines. Made from high-dielectric strength fiberglass, each stick delivers dependable insulation while remaining lightweight and maneuverable.

Note: The Universal Sticks and Switch Head Sticks are supplied without fittings.

Universal Stick w/Universal Base

Slingco Part No.	Description	Length ft (m)	Weight lb (kg)
HLT12961-4	4ft Universal Stick with Universal Base	4 (1.22)	2.26 (1.03)
HLT12961-6	6ft Universal Stick with Universal Base	6 (1.83)	3.00 (1.36)
HLT12961-8	8ft Universal Stick with Universal Base	8 (2.44)	3.77 (1.71)
HLT12961-10	10ft Universal Stick with Universal Base	10 (3.05)	4.52 (2.05)
HLT12961-12	12ft Universal Stick with Universal Base	12 (3.66)	5.27 (2.39)

Switch Head Stick w/Universal Base

Slingco Part No.	Description	Length ft (m)	Weight lb (kg)
HLT12962-4	4ft Switch Head Stick with Universal Base	4 (1.22)	2.51 (1.14)
HLT12962-6	6ft Switch Head Stick with Universal Base	6 (1.83)	3.24 (1.47)
HLT12962-8	8ft Switch Head Stick with Universal Base	8 (2.44)	4.02 (1.82)
HLT12962-10	10ft Switch Head Stick with Universal Base	10 (3.05)	4.77 (2.16)
HLT12962-12	12ft Switch Head Stick with Universal Base	12 (3.66)	5.53 (2.51)



GET IN TOUCH

☎ 1 888 685 9478

✉ sales@slingcoamerica.com

UNIVERSAL AND SWITCH HEAD STICKS

Fittings

Slingco Part No.	Description	Length ft (m)	Weight lb (kg)
ITP14370	Universal Disconnect Hook	n/a	0.4 (0.17)
ITP14370-P	Fluorescent Universal Disconnect Hook	n/a	0.4 (0.17)

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco America, Inc.


Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

Range dimension overlaps If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



GET IN TOUCH

 1 888 685 9478

 sales@slingcoamerica.com